



FW MURPHY®
PRODUCTION CONTROLS



Official FW Murphy Distributor
PT. ATAMORA TEHNIK MAKMUR

Centurion® Series Centurion® Configurable Controller



The Centurion C5 Configurable Controller is the core of the Centurion control and monitoring system. The C5 Controller puts users in control with diagnostics that reduce troubleshooting, improve communication and enhance data management.

- Fully configurable control and monitoring system with applications for reciprocating/screw compressors and pump systems
- Expandable system to meet most three- or four-stage compressor applications
- User configurability with Windows-based software allows the operator to point and click to implement standard processes, and if authorized, configure the I/O points
- No programming experience required
- Local and remote communications, Modbus RTU via RS485/232/Ethernet
- USB 1.1 / 2.0 support for laptops without a serial port
- Upload/download capabilities for configurations and set points
- Shut-down history list (Last 20 events)
- Event history list (Last 32 events)
- Active alarm list
- 10 configurable maintenance timers
- Run hourmeter
- Support for no-flow totalization using lubricator pulses
- Short cycle start protection / starts per hour (electric motor)
- Eight control loops (ISA PID or Linear)
- Configuration templates provided for simple use
- Configurations stored in non-volatile flash memory
- Set points stored in non-volatile EEPROM memory
- Production Programmable, CS&S can modify to meet customer requirements without engineering support
- CAN capable, to support electronic engines
- One core module for Standard and Custom applications
- DIN Rail Mountable
- View EICS and Centurion systems on one M-View® Touch screen display
- Ability to upgrade your older Centurion LCD display to the M-View for higher resolution, less scrolling and brighter backlight
- Diagnostics that reduce troubleshooting
- World-class certifications and harmonized international standards
- Future-proof and backward compatible
- All non-incendive inputs
- Compressor Rod Load calculation, alarm and shutdown

HEAD OFFICE, MARKETING & BUSINESS DEVELOPMENT

Equity Tower, 25th Floor, Suite 25F, SCBD Lot 9,
Jl. Jend. Sudirman Kav. 52-53, Jakarta Selatan, 12190 - Indonesia
Phone : (021) 5154560, 5154561, Fax: (021) 6326748, 5154563
Mobile Phone : 081310787177 (Products)
email : products@atamora.co.id | atamora@atamora.co.id

OPERATION OFFICE

Jl. Ternate 21H, Jakarta Pusat 10150 - Indonesia
Phone: (021) 6326740, 6327177 (Hunting)



<https://www.atamora.co.id>



@atamoraofficial



FW MURPHY®
PRODUCTION CONTROLS



Official FW Murphy Distributor
PT. ATAMORA TEHNIK MAKMUR

Centurion® Series Centurion® Configurable Controller

Overview

Primarily designed for engine/electric motor driven compressors, the Centurion is well suited for many control applications using standard configurations to save money and reduce training. Additionally, FW Murphy specializes in custom designing control packages to meet exact specifications for a variety of applications.

Continuously monitoring input signals, set points and command outputs to maintain proper operation, the Centurion C5 Controller will stop, shut down or control equipment to change conditions when an out-of-limits event occurs. The auto-start capabilities of the Centurion allow for start/stop based on parameters such as pressure set points or by digital signals.

The Centurion provides real-time data via communication ports to a connected display and any remote monitoring system through Ethernet and serial methods.

Specifications

This Centurion consists of one C5 main I/O module, one M-View display module and the option of adding MX4-R2 and MX5-R2 expansion I/O modules. The Centurion is designed for use only within a weatherproof enclosure. No special cables required.

C5 Series Main I/O Module

- Operating temperature: -40° to 185° F (-40° to 85° C)
- Power input: 30 W max 10-30 VDC
- Configuration: PC-based Centurion Configuration software
- Application firmware:
 - Standard offers a user-configurable experience
 - Centurion Custom option offers highly customized applications. Integrate with Rockwell Automation Processors as I/O module to write IEC 61131-3 logic (ladder logic, structured text, function block diagram).
- All I/O options individually software selectable: No jumpers required
- Clock: Battery backed internal real-time clock, approximately 10 years unpowered service life
- 12 Analog inputs*:
 - 0-24 mA or 0-5 VDC, 15-bit hardware
 - 4 resistive potentiometer measurement
- 32 Digital inputs*:
 - NO or NC (active high/active low) intrinsically safe
 - Optically isolated DC digital inputs (active high/active low) with LED indicators
 - Polarity sense / wire fault detection on normally closed systems
 - Approved for use with general purpose switches in hazardous areas
- Eight temperature inputs*:
 - J or K type thermocouples (ungrounded)
 - 3-wire 100Ω Pt RTD temperature inputs***
 - Open, short DC-, short DC+ wire fault detection
 - Cold junction compensation
- One magnetic pickup input/AC run signal:
 - 30 to 10 kHz, 4.5 VAC rms min, 120 VAC rms max
- 10 digital outputs:
 - LED indicators:
 - 4 relay outputs, form C, dry contacts
 - 4 FET outputs (source)
 - 2 FET outputs (sink)
- Four analog outputs:

HEAD OFFICE, MARKETING & BUSINESS DEVELOPMENT

Equity Tower, 25th Floor, Suite 25F, SCBD Lot 9,
Jl. Jend. Sudirman Kav. 52-53, Jakarta Selatan, 12190 - Indonesia
Phone : (021) 5154560, 5154561, Fax: (021) 6326748, 5154563
Mobile Phone : 081310787177 (Products)
email : products@atamora.co.id | atamora@atamora.co.id

OPERATION OFFICE

Jl. Ternate 21H, Jakarta Pusat 10150 - Indonesia
Phone: (021) 6326740, 6327177 (Hunting)



<https://www.atamora.co.id>



@atamoraofficial



FW MURPHY®
PRODUCTION CONTROLS



Official FW Murphy Distributor
PT. ATAMORA TEHNIK MAKMUR

Centurion® Series Centurion® Configurable Controller

- 4-20 mA, 16-bit hardware
- 11 Communication ports:
 - Two SERIAL RS232:
 - Protocol: Modbus RTU (server)
 - Two SERIAL RS485:
 - Protocol: Modbus RTU (server)
 - One USB: host type A (data log access, firmware updates)
 - One USB: interface type B (configuration / firmware updates)
 - Two CAN:
 - One proprietary for FW Murphy hardware
 - One reserved for J1939 Engine ECU
 - Two Ethernet 10/100 (DLR):
 - Protocol: Modbus TCP/IP (server)
 - EtherNet/IP (CIP)
 - One WiFi: Optional C5-1 only
- Third-party approvals:
 - Class I, Div 2, Grps A, B, C, D Haz. Loc. T4
 - Class I, Zone 2, AEx ec [ic] nC IIC T4 Gc, Ex ec [ic] nC IIC T4 Gc X
 - ATEX Zone 2
 - II 3G Ex ec [ic] nC IIC T4 Gc
 - DEMKO 18 ATEX 1926X
 - -40°C < Tamb < +85°C
 - IECEx Zone 2
 - Ex ec [ic] nC IIC T4 Gc
 - IECEx UL 18.0072X
 - -40°C < Tamb < +85°C

MX4-R2 Expansion I/O Module

- Operating Temperature: -40° to 185° F (-40° to 85° C)
- Power input: 14.1 W max 10-30 VDC
- Configuration: PC-based Centurion Configuration software
- 18† thermocouple inputs*: J or K type thermocouples (ungrounded)
- 9† 3-wire 100Ω Pt RTD temperature inputs*, ***
 - Open, short DC-, short DC+ wire fault detection
 - Cold junction compensation
- One magnetic pickup input* / AC Run Signal: 4.5 VAC – 120 VAC, 30 Hz – 10 kHz
- Third-party approvals:
 - Class I, Div 2, Grps A, B, C, D Haz. Loc. T4
 - Class I, Zone 2, AEx ec [ic] IIC T4 Gc, Ex ec [ic] IIC T4 Gc X
 - ATEX Zone 2
 - II 3G Ex ec [ic] IIC T4 Gc
 - DEMKO 18 ATEX 1926X
 - -40°C < Tamb < +85°C
 - IECEx Zone 2

HEAD OFFICE, MARKETING & BUSINESS DEVELOPMENT

Equity Tower, 25th Floor, Suite 25F, SCBD Lot 9,
Jl. Jend. Sudirman Kav. 52-53, Jakarta Selatan, 12190 - Indonesia
Phone : (021) 5154560, 5154561, Fax: (021) 6326748, 5154563
Mobile Phone : 081310787177 (Products)
email : products@atamora.co.id | atamora@atamora.co.id

OPERATION OFFICE

Jl. Ternate 21H, Jakarta Pusat 10150 - Indonesia
Phone: (021) 6326740, 6327177 (Hunting)



<https://www.atamora.co.id>



@atamoraofficial



FW MURPHY®
PRODUCTION CONTROLS



Official FW Murphy Distributor
PT. ATAMORA TEHNIK MAKMUR

Centurion® Series Centurion® Configurable Controller

- Ex ec [ic] IIC T4 Gc
- IECEx UL 18.0072X
- -40°C < Tamb < +85°C

MX5-R2 Expansion I/O Module

- Operating temperature: -40° to 185° F (-40° to 85° C)
- Power input: 16.5 W max 10-30 VDC
- Configuration: PC-based Centurion Configuration software
- 24++Digital inputs*:
 - NO or NC (active high/active low) intrinsically safe
 - Optically isolated DC digital inputs (active high/active low) with LED indicators
 - Polarity sense / wire fault detection on normally closed systems
 - Approved for use with general purpose switches in hazardous areas
- 10 analog inputs*: 0-24 mA or 0-5 VDC, 15 bit hardware
- 6 std. config./ 16*** digital outputs: FET (sink)
- 4 analog outputs: 4-20 mA, 16 bit hardware
- 1 magnetic pickup input* /AC Run Signal: 4.5 VAC -120 VAC, 30 Hz to 10 kHz
- Third-party approvals:
 - Class I, Div 2, Grps A, B, C, D Haz. Loc. T4
 - Class I, Zone 2, AEx ec [ic] IIC T4 Gc, Ex ec [ic] IIC T4 Gc X
 - ATEX Zone 2
 - II 3G Ex ec [ic] IIC T4 Gc
 - DEMKO 18 ATEX 1926X
 - -40°C < Tamb < +85°C
 - IECEx Zone 2
 - Ex ec [ic] IIC T4 Gc X
 - IECEx UL 18.0072X
 - -40°C < Tamb < +85°C

* Non-incendive (digital inputs, analog inputs and temperature inputs are intrinsically safe and non-incendive).

++ Applies only to Centurion™ Custom and Rockwell Automation® Processor configurations.

*** RTD=Resistive Temperature Device, American RTD Standard, TCR 0.00392, units Ohms / Ohm / deg. between 0-100 C.

† When configured for an RTD channel, two consecutive odd/even T/C channels are consumed.

M-VIEW® Monochrome Display MV-5-C

- Operating temperature: -40° to 185° F (-40° to 85° C)
- Power input: 11 W max 10-30 VDC
- Screen: 320 x 240 pixels, LCD display with backlight
- User interface: 12-key keypad set point entry, alarm acknowledgment, start, stop, reset, etc.
- Communications:
 - RS232-1/RS485-1 (Modbus RTU client)
 - RS485-2 (Modbus RTU server)
 - 1 USB interface type B (firmware updates)
 - 1 USB host type A (reserved)
 - CAN x 2
 - 1 proprietary for FW Murphy hardware
 - 1 reserved for J1939 engine ECU

HEAD OFFICE, MARKETING & BUSINESS DEVELOPMENT

Equity Tower, 25th Floor, Suite 25F, SCBD Lot 9,
Jl. Jend. Sudirman Kav. 52-53, Jakarta Selatan, 12190 - Indonesia
Phone : (021) 5154560, 5154561, Fax: (021) 6326748, 5154563
Mobile Phone : 081310787177 (Products)
email : products@atamora.co.id | atamora@atamora.co.id

OPERATION OFFICE

Jl. Ternate 21H, Jakarta Pusat 10150 - Indonesia
Phone: (021) 6326740, 6327177 (Hunting)



<https://www.atamora.co.id>



@atamoraofficial



FW MURPHY®
PRODUCTION CONTROLS




Official FW Murphy Distributor
PT. ATAMORA TEHNIK MAKMUR

Centurion® Series Centurion® Configurable Controller

- Customizable process screens (up to nine):
 - Line by line
 - Gage
 - Control loop
 - Generic register
- Built-in screens (examples):
 - Digital input status and polarity
 - Digital input status and polarity
 - Digital output status
 - Temperature input status/fault
 - Fault snapshot (mirror of line by line)
 - Alarm log
- Third-party approvals:
 - Class I, Div 2, Grps A, B, C, D Haz. Loc. T4
 - Class I, Zone 2, AEx ec ic [ic] IIC T4 Gc, Ex ec ic [ic] IIC T4 Gc X
 - ATEX Zone 2
 - II 3G Ex ec ic [ic] IIC T4 Gc
 - DEMKO 18 ATEX 1926X
 - -40°C < Tamb < +85°C
 - IECEx Zone 2
 - Ex ec ic [ic] IIC T4 Gc
 - IECEx UL 18.0072X
 - -40°C < Tamb < +85°C

M-VIEW® Touch Displays MV-7T and MV-12T

- Operating temperature: -4° to 140° F (-20° to 60° C)
- Power input:
 - MV-7T, 15 W max 10-30 VDC (36 W max with modules)
 - MV-12T, 23 W max 10-30 VDC (57 W max with modules)
- Screen (sunlight readable):
 - MV-7T, 800×480 pixels, 7" widescreen, brightness 1000 cd/m2
 - MV-12T, 1280×800 pixels, 12" widescreen, brightness 1600 cd/m2
- User interface: resistive analog touchscreen
- Communication interface:
 - 2x RS232
 - 1x RS485
 - 2x USB host type A (file transfer, datalogging, USB device)
 - 1x USB server (program/firmware updates)
 - 2 Ethernet 10/100 Base TX (RJ45)
- Communication protocols:
 - EtherNet/IP (CIP)
 - Modbus TCP/IP
 - Modbus RTU standard
 - 300 plus available, web server



HEAD OFFICE, MARKETING & BUSINESS DEVELOPMENT

Equity Tower, 25th Floor, Suite 25F, SCBD Lot 9,
Jl. Jend. Sudirman Kav. 52-53, Jakarta Selatan, 12190 - Indonesia
Phone : (021) 5154560, 5154561, Fax: (021) 6326748, 5154563
Mobile Phone : 081310787177 (Products)
email : products@atamora.co.id | atamora@atamora.co.id

OPERATION OFFICE

Jl. Ternate 21H, Jakarta Pusat 10150 - Indonesia
Phone: (021) 6326740, 6327177 (Hunting)



<https://www.atamora.co.id>



@atamoraofficial




FW MURPHY®
PRODUCTION CONTROLS



Official FW Murphy Distributor
PT. ATAMORA TEHNIK MAKMUR

Centurion® Series Centurion® Configurable Controller

- Third-party approvals:
 - CE Approved
 - EN 61326-1 Immunity to Industrial Locations Emission CISPR 11 Class A
 - IEC/EN 61010-1
 - RoHS compliant
 - ATEX Approved
 - II 3 G Ex ic nA IIC T4 Gc
 - II 3 D Ex tc IIIC T135°C Dc
 - DEMKO 14 ATEX 1387X
 - EN 60079-0, -11, -15, -31
 - IECEx Approved
 - Ex ic nA IIC T4 Gc
 - Ex tc IIIC T135°C Dc
 - IECEx UL 15.0035X
 - IEC 60079-0, -11, -15, -31
 - UL Approved
 - cULus Listed for Ordinary Location: File #E302106
 - UL 61010-1, -2-201
 - cULus Listed for Hazardous Location: File #E317425
 - Class I, Division 2, Groups A, B, C and D
 - Class II, Division 2, Groups F and G
 - Class III, Division 2 ANSI/ISA 12.12.01, C22.2 No. 213-M1987, 157-92
 - IP66 enclosure rating (face only)
 - Type 4X outdoor enclosure rating (face only)
 - ABS type approval for shipboard applications



HEAD OFFICE, MARKETING & BUSINESS DEVELOPMENT

Equity Tower, 25th Floor, Suite 25F, SCBD Lot 9,
Jl. Jend. Sudirman Kav. 52-53, Jakarta Selatan, 12190 - Indonesia
Phone : (021) 5154560, 5154561, Fax: (021) 6326748, 5154563
Mobile Phone : 081310787177 (Products)
email : products@atamora.co.id | atamora@atamora.co.id

OPERATION OFFICE

Jl. Ternate 21H, Jakarta Pusat 10150 - Indonesia
Phone: (021) 6326740, 6327177 (Hunting)



<https://www.atamora.co.id>



@atamoraofficial

Centurion™ C5 Series Configurable Controller

The Centurion Configurable Controller is a control and monitoring system. Primarily designed for engine/electric motor-driven compressors, the Centurion is well suited for many control applications using standard configurations to save money and reduce training. Additionally, we can custom design a control package to meet exact specifications for a variety of applications.

The Centurion continuously monitors input signals and set points and commands outputs to maintain proper operation. When an out-of-limits event occurs, the controller will stop, shut down or control equipment to change conditions. The auto-start capabilities of the Centurion allow for start/stop based on parameters such as pressure set points or by digital signals.

The Centurion provides real-time data via communication ports to a connected display and/or supervisory system. This advanced system offers multiple options for remote communications and operation including HMI's, PLC's, PC's and SCADA systems. The industry-standard Modbus RTU protocol means greater support for a wide variety of communication equipment including radio and satellite communications systems.



Features

- Fully configurable control and monitoring system. Applications include reciprocating/screw compressors and pump systems.
- Expandable system to meet most three-to four-stage compressor applications.
- User configurability with Windows-based software allows the operator to point and click to implement standard processes. All I/O points can be custom configured.
- No programming experience required.
- Local and remote communications, Modbus RTU via RS485/232/Ethernet.
- USB 1.1/2.0 support for laptops without a serial port.
- Upload/download capabilities for configurations and set points.
- Shut-down history list (Last 20 events).
- Event history list (Last 32 events).
- Active alarm list.
- 10 configurable maintenance timers.
- Run hourmeter.
- Support for no-flow totalization using lubricator pulses.
- Short cycle start protection / starts per hour (electric motor).
- Eight control loops, closed loop PID / open loop linear.
- Configuration templates provided for simple use.
- Configurations stored in non-volatile flash memory.
- Set points stored in non-volatile EEPROM memory.
- CAN capable, to support electronic engines.
- Same core module for Centurion Configurable and Centurion Custom applications.
- View EICS® and Centurion systems on one M-View® touch screen display.
- Diagnostics that reduce troubleshooting.
- World-class certifications and harmonized international standards.
- Future-proof and backward compatible.
- All non-incendive inputs.
- Compressor rod load calculation, alarm and shutdown.

Basic Components

The Centurion consists of a display module, a main I/O module and optional expansion I/O module and choice of M-View Series display. No special cables are required. The Centurion is designed for use within a weatherproof enclosure only.

C5, Main I/O Module:

Centurion C5 Configurable Controller

(Optional) MX4-R2 Expansion I/O Module:


(Optional) MX5-R2 Expansion I/O Module:

Display: Choose from

MV-5-C, MV-7T or MV-12T

C5 Series Main I/O Module


- Operating temperature: -40° to 185° F (-40° to 85° C)
- Power input: 30 W max 10-30 VDC
- Configuration: PC-based Centurion Configuration Software
- Application firmware:
 - Standard offers a user-configurable experience
- All I/O options individually software selectable: No jumpers required
- Clock: Battery backed internal real-time clock, approximately 10 years unpowered service life
- 12 Analog inputs*:
 - 0-24 mA or 0-5 VDC, 15-bit hardware
 - 4 configurable for resistive potentiometer measurement
- 32 Digital inputs*:
 - NO or NC (active high/active low) intrinsically safe
 - Optically isolated DC digital inputs (active high/active low) with LED indicators
 - Polarity sense / wire fault detection on normally closed systems
 - Approved for use with general purpose switches in hazardous areas
- Eight temperature inputs*:
 - J or K Type Thermocouples (ungrounded)
 - 3-wire 100Ω Pt RTD temperature inputs***
 - Open, short DC-, short DC+ wire fault detection
 - Cold junction compensation
- One magnetic pickup input/AC run signal:
 - 30 to 10 kHz, 4.5 VAC rms min, 120 VAC rms max.
- 10 digital outputs:
 - LED indicators:
 - 4 relay outputs, form C, dry contacts
 - 4 FET outputs (source)
 - 2 FET outputs (sink)
- Four analog outputs:
 - 4-20 mA, 16-bit hardware
- 11 Communication ports:
 - Two SERIAL RS232:
 - > Protocol: Modbus RTU (server)
 - Two SERIAL RS485:
 - > Protocol: Modbus RTU (server)
 - One USB: Host Type A (data log access, firmware updates)
 - One USB: Server Type B (configuration/firmware updates)
- Two CAN:
 - > One proprietary for FW Murphy hardware
 - > One reserved for J1939 Engine ECU
- Two Ethernet 10/100 (DLR), Single MAC ID:
 - > Protocol: Modbus TCP/IP (server)
 - > EtherNet/IP (CIP)
- One Wi-Fi: Optional C5-1 only
- Third-party approvals:
 - North America:
 - Class 1, Div 2, Grps A, B, C, D Haz. Loc. T4
 - Class I, Zone 2, AEx ec [ic] nC IIC T4 Gc Ex ec [ic] nC IIC T4 Gc X
 - ATEX Zone 2
 - II 3G Ex ec [ic] nC IIC T4 Gc
 - DEMKO 18 ATEX 1926X
 - 40°C ≤ Tamb ≤ +85°C
 - IECEX Zone 2
 - Ex ec [ic] nC IIC T4 Gc
 - IECEX UL 18.0072X
 - 40°C ≤ Tamb ≤ +85°C



Expansion I/O Modules


MX4-R2 Expansion I/O Module

- Operating Temperature: -40° to 185° F (-40° to 85° C)
- Power input: 14.1 W max 10-30 VDC
- Configuration: PC-based Centurion Configuration Software
- 18[†] thermocouple inputs*: J or K Type thermocouples (ungrounded)
- 9[†] 3-wire 100Ω Pt RTD temperature inputs*, ***
 - Open, short DC-, short DC+ wire fault detection
 - Cold junction compensation
- One magnetic pickup input* / AC Run Signal: 4.5 VAC – 120 VAC, 30 Hz – 10 kHz
- Third-party approvals:
 - Class 1, Div 2, Grps A, B, C, D Haz. Loc. T4
 - Class I, Zone 2, AEx ec [ic] IIC T4 Gc Ex ec [ic] IIC T4 Gc X
 - ATEX Zone 2
 - II 3G Ex ec [ic] IIC T4 Gc
 - DEMKO 18 ATEX 1926X
 - 40°C ≤ Tamb ≤ +85°C
 - IECEX Zone 2
 - Ex ec [ic] IIC T4 Gc
 - IECEX UL 18.0072X
 - 40°C ≤ Tamb ≤ +85°C



MX5-R2 Expansion I/O Module

- Operating temperature: -40° to 185° F (-40° to 85° C)
- Power input: 16.5 W max 10-30 VDC
- Configuration: PC-based Centurion Configuration Software
- 10 analog inputs*: 0-24 mA or 0-5 VDC, 15 bit hardware
- 16 digital outputs: FET (sink)
- 4 analog outputs: 4-20 mA, 16 bit hardware
- 1 magnetic pickup input* / AC Run Signal: 4.5 VAC -120 VAC, 30 Hz to 10 kHz
- Third-party approvals:
 - Class 1, Div 2, Grps A, B, C, D Haz. Loc. T4
 - Class I, Zone 2, AEx ec [ic] IIC T4 Gc Ex ec [ic] IIC T4 Gc X
 - ATEX Zone 2
 - II 3G Ex ec [ic] IIC T4 Gc
 - DEMKO 18 ATEX 1926X
 - 40°C ≤ Tamb ≤ +85°C
 - IECEX Zone 2
 - Ex ec [ic] IIC T4 Gc X
 - IECEX UL 18.0072X
 - 40°C ≤ Tamb ≤ +85°C



*Non-incendive. (Digital Inputs, Analog Inputs and Temperature Inputs are intrinsically safe and non-incendive.)

***RTD=Resistive Temperature Device, American RTD Standard, TCR 0.00392, units Ohms/Ohm / deg. between 0-100 C.

[†] When configured for an RTD channel, two consecutive odd/even T/C channels are consumed.

MV-5-C, M-View® Monochrome LCD Display

- Operating temperature: -40° to 185° F (-40° to 85° C)
- Power input: 11 W max 10-30 VDC
- Screen: 320 x 240 pixels, LCD display with backlight
- User interface: 12-key keypad set point entry, alarm acknowledgment, start, stop, reset, etc.
- Communications:
 - RS232-1/RS485-1 (Modbus RTU client)
 - RS485-2 (Modbus RTU server)
 - 1 USB Server Type B (firmware updates)
 - 1 USB Host Type A (reserved)
 - CAN x 2
 - >1 proprietary for FW Murphy Hardware
 - >1 reserved for J1939 engine ECU
- Customizable process screens (up to nine):
 - Line by line
 - Gauge
 - Control loop
 - Generic register
- Built-in screens (examples):
 - Digital input status and polarity
 - Digital output status
 - Temperature input status/fault
 - Fault snapshot (mirror of line by line)
 - Alarm log
 - Event log
- Third-party approvals:
 - North America:
 - Class 1, Div 2, Grps A, B, C, D Haz. Loc. T4
 - Class I, Zone 2, AEx ec ic [ic] IIC T4 Gc Ex ec ic [ic] IIC T4 Gc X
 - ATEX Zone 2
 - II 3G Ex ec ic [ic] IIC T4 Gc
 - DEMKO 18 ATEX 1926X
 - 40°C ≤ Tamb ≤ +85°C
 - IECEx Zone 2
 - Ex ec ic [ic] IIC T4 Gc
 - IECEx UL 18.0072X
 - 40°C ≤ Tamb ≤ +85°C




MV-7T and MV-12T, M-View® Touch Series Displays

- Operating temperature: -4° to 140° F (-20° to 60° C)
- Power input:
 - MV-7T, 15 W max 10-30 VDC (36 W max with modules)
 - MV-12T, 23 W max 10-30 VDC (57 W max with modules)
- Screen (sunlight readable):
 - MV-7T, 800x480 pixels, 7" widescreen, brightness 1000 cd/m2
 - MV-12T, 1280x800 pixels, 12" widescreen, brightness 1600 cd/m2
- User interface: resistive analog touchscreen
- Communication interface
 - 2x RS232
 - 1x RS485
 - 2x USB host type A (file transfer, datalogging, USB device)
 - 1x USB server (program/firmware updates)
 - 2 Ethernet 10/100 Base TX (RJ45)
- Communication protocols:
 - EtherNet/IP (CIP)
 - Modbus TCP/IP
 - Modbus RTU standard
 - 300 plus available, web server
- Third-party approvals:
 - CE approved
 - EN 61326-1 immunity to industrial Locations emission CISPR 11 Class A
 - IEC/EN 61010-1
 - RoHS compliant
 - ATEX approved
 - II 3 G Ex ec ic nA IIC T4 Gc
 - II 3 D Ex tc IIIC T135°C Dc
 - DEMKO 14 ATEX 1387X
 - EN 60079-0, -11, -15, -31
 - IECEx approved
 - Ex ic nA IIC T4 Gc
 - Ex tc IIIC T135°C Dc
 - IECEx UL 15.0035X
 - IEC 60079-0, -11, -15, -31
 - UL approved
 - cULus listed for ordinary location: File #E302106
 - 2-201
 - cULus listed for hazardous location: File #E317425
 - Class I, Division 2, Groups A, B, C and D
 - Class II, Division 2, Groups F and G
 - Class III, Division 2 ANSI/ISA 12.12.01, C22.2 No. 213-M1987, 157-92
 - IP66 enclosure rating (face only)
 - Type 4X outdoor enclosure rating (face only)
 - ABS type approval for shipboard applications




Dimensions

C5 Series




Dimensions (continued)


MV-5-C




MV-7T



MV-12T



Side-by-Side Screen Approximate Sizes



How to Order

Select a Centurion Configurable Controller.

- C5

Specify expansion I/O modules (optional).

- MX4-R2 or MX5-R2

Specify a display.

- MV-5-C, MV-7T or MV-12T

The minimum system requirements:

- C5 Main I/O Module
- Display capable of Modbus communications

The FW Murphy M-View Series displays are highly integrated HMIs for use with the Centurion system and are recommended for most customers.

Some systems may require additional I/O which is available on the MX4-R2 or MX5-R2 expansion I/O modules.

Part Number	Description	Notes
Specify Model	C5, Centurion Controller (Main Module)	Centurion C5 Configurable Controller
	MV-5-C, (5 in. monochrome LCD display)	Standard, Auto sync to C5
	MV-7T, (7 in. touchscreen full-color display)	Optional, Auto sync to C5
	MV-12T, (12 in. touchscreen full-color display)	
50703852	MX4-R2 expansion I/O module	Optional
50703853	MX5-R2 expansion I/O module	
50000774	Ignition noise (choke) filter	
00032696	C5 Plug kit	Printed replacement terminal plugs for main I/O module
00032656	MX4-R2 Plug kit	Printed replacement terminal plugs for MX4-R2 expansion I/O module
00032657	MX5-R2 Plug kit	Printed replacement terminal plugs for MX5-R2 expansion I/O module
50702313	Centurion configuration tool for user application setup	Centurion configuration tool is software for modifying sequence of operation, set points, timers, faults and displays for Centurion. Includes file transfer utilities for configuration and upgrades.

Approximate Shipping Weight and Dimensions

Model	Weight	Dimension
C5 Controller	2 lb. 7 oz.	16 x 11 x 5 in.
MV-5-C Display	2 lb. 4 oz.	8 x 8 x 6 in.
MV-7T Display	3 lb. 4 oz.	10 x 10 x 6 in.
MV-12T Display	5 lb. 1 oz.	10 x 12 x 12-1/4

Approximate Shipping Weight and Dimensions

Model	Weight	Dimension
MX4-R2 expansion I/O module	1 lb. 6 oz.	12 x 7 x 5 in.
MX5-R2 expansion I/O module	1 lb. 6 oz.	12 x 7 x 5 in.
C5 Plug kit	0 lb. 5 oz.	5 x 5 x 5
MX4-R2 Plug kit	0 lb. 3 oz.	5 x 5 x 5
MX5-R2 Plug kit	0 lb. 3 oz.	5 x 5 x 5